



OAK ORE

Reminiscent of the warm, dark earth from which ore is mined, Oak Ore has a rich, warm tone creating a comforting, grounded base. The subtle variation in colour and nuances reflects the visual of a corroded surface shifting from light to dark, while still establishing a unity achieved by the overlaying soft, brown stain. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	133NCDEKB9KW240 / 7393969302654
Design / Wood Species	3-strip / Oak
Surface treatment / Natural/Stained	Matt lacquer / Stained
Width x Length x Thickness	200 x 2423 x 13 mm
Weight per package / per m2	24.5 kg / 7.21 kg
Area per package / per pallet	3.4 m ² / 170 m ²
Grading	Lively
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 2.6 mm
Resandable	2-3 times
Core material	Pine/Spruce/Alder
Backside material	Veneer
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9

PRODUCT DETAILS		
LRV / LRV Std1 / LRV Std2	26 / 4 / 8	
Warranty	20 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density	>500 kg/m³	
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	.09 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - minor noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK SALT



OAK ORE



OAK CRYSTAL



OAK FLINT