



OAK SILK

Oak Silk has a silky white stain adding a soft, slightly muted expression to this 2-strip oak floor. The natural knots add character and beauty, while the elegant format and precision milling complete this sophisticated, almost seamless, look. It is finished with a matt lacquer, eliminating glare and protecting the wood from daily wear making Oak Silk a floor of understated beauty.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	152N60EKP9KW240 / 7393969302197	
Design / Wood Species	2-strip / Oak	
Surface treatment /	Matt lacquer / Stained	
Natural/Stained		
Width x Length x Thickness	200 x 2423 x 15 mm	
Weight per package / per	23 kg / 7.9 kg	
m2		
Area per package / per	2.91 m ² / 130.95 m ²	
pallet		
Grading	Lively	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer thickness	3.5 mm	
Resandable	2-3 times	
Core material	Pine/Spruce/Alder	
Backside material	Spruce Veneer	
Hardness (Brinell) value	3,7	

PRODI	ICT	DETAILS	
PRODU	J C I	DETAILS	

LRV / LRV Std1 / LRV Std2	34 / 4.3 / 8.6	
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD















DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes sound and black knots. Knots can be present in all sizes and numbers.

Colour change: Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK SILK



OAK SHELL



OAK BROWNIE



OAK ALLOY





OAK ALE



OAK CREME



OAK GRANITE



OAK LIMESTONE