



CHASSIS® PRO

Classification	ASTM F 1700 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.80 mm x 1219.20 mm
Overall Thickness*	0.12" / 3.0 mm (nom)
Wear Layer	20 mil / 0.50 mm featuring Tuff Shield finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	Lifetime Residential / 30-Year Light Commercial
Recycled Content	This product contains recycled content.
Packaging	27.98 ft² (2.60 m²) per carton 12 pieces per carton 65 cartons per pallet
Weight Per Carton	32.88 lbs / 14.91 kg




Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, ≥ 0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC	ASTM E 492	61
IIC	ASTM E 989	67



PREMIUM WEAR LIMITED WARRANTY



Axle CPR 9255



Clutch CPR 9256




Spitfire CPR 9257 (Heavy Shade Variation)



Backbone CPR 9258 (Heavy Shade Variation)




Caspas CPR 9259



Armature CPR 9260 (Heavy Shade Variation)



Motorcoach CPR 9261



Suspension CPR 9262

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.