


A LUXURY VINYL SHEET FLOOR AT A VALUE PRICE POINT.

# CustomPro™

FIBERFLOOR® PRO SERIES



CORAWOOD | MOUSE | 15143

For customers that want a luxury vinyl sheet floor at a value price point, CustomPro™ is the perfect choice. This floor is cost-effective, easy to maintain, and stylish, making CustomPro™ ideal for renovation or new construction of homes, apartments, and multifamily units. CustomPro™ is **CERTIFIED asthma & allergy friendly®** by Allergy Standards LTD, making it a better choice for all residents, including those impacted by asthma and allergies.




ORTHO-PHTHALATE  
FREE


 **Tarkett**  
*Home*



# Tarkett FiberFloor® – CustomPro™




**15001 | Vermont Slate**  
Mushroom  
36" x 28.8", 14.4" Drop, DNR



**15004 | Vermont Slate**  
Charcoal  
36" x 28.8", 14.4" Drop, DNR



**15071 | Atlas**  
Ibis White  
36" x 72", DNR



**15072 | Atlas**  
Marble Grey  
36" x 72", DNR




**15081 | Bridge Stone**  
Desert Stone  
36" x 36", DNR



**15101 | Brentwood**  
Manchester  
36" x 48", 12" Drop, DNR




**15121 | Barn Jazz**  
Warm Grey  
36" x 72", 18" Drop, DNR



**15141 | Corawood**  
Dark Bronze  
48" x 72", DNR




**15142 | Corawood**  
Wheat  
48" x 72", DNR



**15213 | Corawood**  
Mouse  
48" x 72", DNR



**15144 | Corawood**  
Charcoal  
48" x 72", DNR



**15151 | Modern Slate**  
Cliff  
36" x 72", DNR



**15161 | Longwood**  
Cocoa  
36" x 36", 18" Drop, DNR



**15162 | Longwood**  
Caramel  
36" x 36", 18" Drop, DNR



**15181 | Sylvanova Slate**  
Mid Grey  
36" x 36", DNR



**15201 | Canyon Slate**  
Desert  
36" x 48", 12" Drop, DNR



**15221 | Summerville**  
Copper  
48" x 36", 18" Drop, DNR




**15251 | Mendoza**  
Warm Grey  
36" x 36", 9" Drop, DNR



**15252 | Mendoza**  
Tan  
36" x 36", 9" Drop, DNR



**15261 | Lexington Plank**  
Fossil  
36" x 36", 18" Drop, DNR




**15272 | Legend**  
Almond  
18" x 18", Reverse



**15281 | Arizona Stone**  
Terragris  
36" x 36", 18" Drop, DNR



**15291 | Cliff Oak**  
Gunstock  
36" x 36", 18" Drop, DNR




**15292 | Cliff Oak**  
Chocolate  
36" x 36", 18" Drop, DNR



**15504 | White Oak**  
Weathered  
36" x 36", 18" Drop, DNR



**15505 | White Oak**  
Natural  
36" x 36", 18" Drop, DNR



**15543 | Mojave Slate**  
Storm  
36" x 48", 12" Drop, DNR



Visit  
[TarkettHome.com](https://www.TarkettHome.com)  
for complete  
warranty details.

## Specifications

|                                                                                                                                   |                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| Series                                                                                                                            | 15XXX                                                   |
| Nominal Total Thickness                                                                                                           | 55 mils (0.055"/1.40 mm)                                |
| Wear Layer Thickness                                                                                                              | 10 mils (0.01"/0.254 mm)                                |
| Wear Layer Finish                                                                                                                 | Urethane (Low Gloss)                                    |
| Width                                                                                                                             | 12' (3.6 m)                                             |
| Standard Roll Size                                                                                                                | 201 sq. yd. (168 m <sup>2</sup> )                       |
| Weight per Sq. Yd.                                                                                                                | 2.22 lbs. (1 kg)                                        |
| ASTM F1303                                                                                                                        | Type I, Grade 3, Class C                                |
| ASTM D2047 (Slip)                                                                                                                 | >0.5                                                    |
| ASTM E648 (Fire)                                                                                                                  | >0.45 W/cm <sup>2</sup>                                 |
| ASTM E662 (Smoke)                                                                                                                 | <450                                                    |
| ASTM F137 (Flexibility)                                                                                                           | 1/4" (6.4 mm)                                           |
| ASTM F925 (Staining)                                                                                                              | Excellent                                               |
| ASTM F970 Static Load Limit                                                                                                       | 75 lbs./sq. in. (5.3 kg/cm <sup>2</sup> )               |
| ASTM F1514 (Heat Stability)                                                                                                       | Δ E < 8                                                 |
| ASTM F1515 (Light Stability)                                                                                                      | Δ E < 8                                                 |
| ASTM E2179 (Impact Sound Reductions)                                                                                              | Δ IIC 16 dB                                             |
| Location                                                                                                                          | Below, on and above grade concrete, above grade plywood |
| Adhesive                                                                                                                          | Tarkett QBond-One™                                      |
| Seam Sealer                                                                                                                       | Tarkett DT-65 Seam Sealer                               |
| HUD/FHA Minimum                                                                                                                   | Yes, ≥/0.010" wear layer                                |
| FloorScore® Certification                                                                                                         | SCS-EC10.3-2014: SCS-FS-02746                           |
| CERTIFIED <b>asthma &amp; allergy friendly</b> ® by Allergy Standards Ltd and the Asthma and Allergy Foundation of America (AAFA) |                                                         |
| Certificate AAFC: 1155/11/05/01/2066                                                                                              |                                                         |

## Healthier Home

This product has been certified to meet the requirements of these flooring products certification programs for indoor air quality.



ORTHOPHTHALATE  
FREE

## Tarkett North America

[www.TarkettHome.com](https://www.TarkettHome.com)



Connect with us  
@TarkettHome



Scan this code to visit  
[www.TarkettHome.com/CustomPro](https://www.TarkettHome.com/CustomPro)

For more accurate color  
and pattern representation,  
we suggest you visit an  
authorized Tarkett Home dealer  
to view an actual product sample.