



7096 Ursa

	US Units	Metric Units
Style Number	1024V	
Construction	Residential Resilient - Sheet	
Profile	Direct Glue	
Overall Thickness	0.085"	2.16 mm
Wear Layer Thickness	10 mil (0.01")	0.3 mm
Finish	Opticlean Urethane	
Installation Methods	Direct Glue	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	20 Year Residential Sheet Vinyl Limited Warranty	
Installation	Residential Sheet Flooring Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	

Colors


1006 Dorado

Pattern: 47Inch W x 96Inch L
Drop: 39Inch


1007 Gemini

Pattern: 47Inch W x 96Inch L
Drop: 0Inch


1008 Lynx

Pattern: 39Inch W x 59Inch L
Drop: 39Inch


1067 Pegasus


Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty


2026 Phoenix

Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty


5030 Tucana


Pattern: 39Inch W x 39Inch L
Drop: 13Inch


5031 Norma


Pattern: 39Inch W x 59Inch L
Drop: 39Inch


5032 Leo

Pattern: 39Inch W x 39Inch L
Drop: 13Inch


5034 Aquila

Pattern: 39Inch W x 39Inch L
Drop: 20Inch


5095 Perseus

Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty


5096 Aries


Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty


5098 Aquarius

Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty


7037 Pavo

Pattern: 39Inch W x 59Inch L
Drop: 39Inch


7096 Ursa

Pattern: 0Unknown Empty W x
0Unknown Empty L
Drop: 0Unknown Empty

Suggested Adhesive

Style Name	Style Number
SHAW 350 PS ADH 4G	024VS
SHAW 350 PS ADH 1G	053VS
SHAW SV-1200 1 GAL	100SA
SHAW SV-1200 4 GAL	101SA