

LAMINATE FLOOR

Endurance 14mm Collection

ACS

ENDURANCE



24HRS WATER RESISTANT


Tested by NALFA Standards
North American Flooring Association

Introducing a new laminate floor collection


Endurance offers unparalleled durability in its two versions, 14mm and 8mm thicknesses, ensuring a solid feel underfoot. Crafted with a scratch-resistant aluminum oxide finish, this affordable laminate is the

perfect choice for homeowners seeking long-lasting elegance. Additionally, this flooring boasts multiple layers compacted to perfection, creating stability and strength.

COLLECTION COLORS




14MM AC5 - 24HRS WATER RESISTANT



SPECS

Width	7-1/2"
Length	47-1/4"
Thickness	14mm (12mm + 2mm Pad)
STC	54
IIC	53
Planks/Box	6
Box Weight	33 lbs
SF/Box	14.59
Box/Pallet	44
SF/Pallet	641.96
Pallet/40'CTR	40




INFO & LIVE

SPECS




ACCESSORIES


T-Molding
(TM)




Multi-purpose
(MP)



Flush Stair Nose Square
(FSN)




Stair Tread
(ST)



ACS **ENDURANCE** 14MM INSTALLATION INSTRUCTIONS

1. **Flooring needs to be acclimated.** Stored flat and fully supported during shipping and storage. Allow product, in an unopened package, to condition in the room where installation is to take place at a constant temperature between 64°F and 77°F or 19° – 25°C for a period of 48 hours prior to installation (Fig. 4 & 5).
2. Check flooring for possible defects prior to the installation. **Complaints can only be accepted before installation.** Slight variations in color and textures are designed to enhance its natural appearance. Mixing planks, from 3 to 4 different boxes creates a more realistic look.
3. Be aware that when exposed to **excessive temperatures and direct sunlight flooring will expand and contract causing problems with the locking system.** Please consider these exposures when choosing the area to install your flooring (Fig. 31).
4. **Flooring is not recommended to be installed in facilities with walkers, wheelchairs or extended care use, or in facilities with movement of heavy displays, racks, dentist chairs etc. Do not fix or place any extremely heavy object on top of this floor.** All these types of installations and cases may exert extreme stress and compromise the locking system of the flooring. **Chair mats must be used under office chairs** (Fig. 10, 24 & 25).
5. **Subfloors must be clean of debris, structurally sound, solid, stable, level, plumb,** to ensure no more than 3/16" unevenness per 10-feet span (Fig. 1, 2 & 3).
6. Subfloors presenting vapor emissions more than 2% CM should not be intended unless floor is treated with moisture block. All concrete subfloors must use plastic sheet for extra moisture protection. Parkay Floors® recommends "Plasticguard 6" as the ideal poly block to protect against moisture (Fig. 8).
7. Flooring can be installed over existing firm floors (Linoleum, PVC), non-grout separation tile floors, but **all carpet, wood or laminate floors must be removed.** Moisture barrier sheet must be installed (Fig. 1).
8. Since this floor requires a floating installation, **a minimum expansion gap of 1/2" must be left along the entire perimeter** of the area and fixtures, to allow expansion (Fig. 13).
9. Any flooring area length exceeding 32 Linear Feet must use transition moldings (Fig. 17).
10. A maximum of 10% sheen variation in between planks is consider normal.
11. **Flooring is not recommended to be installed over any electrical radiant heating systems. Only radiant heated system using water are recommended.** Max heating temperate must not exceed 82°F. (Fig. 6). These Instructions must be followed:
 - Before installing, make sure to test the heating system at its maximum capacity to force out any residual moisture and to make sure it's working properly.
 - Moisture content on screed must not exceed 1.5%.
 - Shut down the heating system at least 48 hours prior to installation.
 - Keep room temperate between 64°F and 77°F during the installation.
 - After flooring is install, turn on the heating system gradually, from minimum to maximum within 1-hour period.

12. **Agree with the client on which direction the floor boards should run** since this influences the visual size ratio of the space.
13. **Pre-plan the floor by measuring the room first.** If the width of the last row is less than 2" (5cm) saw the first and the last plank in equal width.
14. **Snap the lines on the substrate to identify the layout reference points.** Planks should be set using this reference to ensure boards are aligned and will lock together correctly.
15. The use of pull bar and tapping block is recommended to ensure a successful install.
16. **Flooring provides a very tight fit.** Proper care must be used to ensure all seams are tight at end of install. An unprofessional installation or use of improper tools can result in damage to the click profiles. Do not lean boxes or planks on a vertical position against the floor, since it might brake the click system.
17. **If more than 5% of the product pulled out of the cartons is showing defects, stop the installation** immediately and contact your, Parkay Floors® representative.
18. **Product cannot be used for exterior applications or wet areas.** Never install on ceilings or countertops (Fig. 32).




Flooring can have slight color variations in between production runs. Before starting the installation, it is best to check the production run # which is indicated on the label on the carton. If you find that you have cartons from different production runs, it is highly recommended that you open cartons and install a mix of planks from each different production run on your floor. This will result in a more natural looking floor.

MAINTENANCE

Clean regularly with a microfiber mop with a laminate floor cleaner, available at your local market. Do not spray excessively, pour liquid directly or leave moisture standing on the laminate floor. Always use chair protectors under furniture and on chair legs. Teflon protectors are best (Fig. 27, 28, 29 & 30).

STEPS TO FOLLOW



WARRANTY

25 years residential / 5 years light commercial warranty

Our 5 years limited light commercial warranty for Parkay Endurance Laminate Floor means that for five years, from the date of purchase from the original owner and first installation of the product, your floor will be free from manufacturing defects and will not wear through when installed and maintained according to instructions supplied with each carton. This warranty applies only to the original end user with a proof of purchase, warranty is not transferable. Floors must have been installed by a licensed and insured professional to be able to process any claim. The guarantee is for replacement or refund of the material only, no labor. Claims for wear must show a minimum dime size area. High-heeled shoes, rolling carts, furniture and chairs without protective pads can damage the floor and are not covered by this warranty.

Warranty covers against: Staining, Wear, Fading as a result of natural or artificial light, damage by moisture from everyday household spills and manufacturing defects. Floor will only be replaced for one of the same monetary value.


If more than 5% of the product pulled out of the cartons is showing defects, stop the installation immediately and contact your Parkay Floors® representative. Transition moldings are not covered under this warranty. Scratches and loss of gloss are not considered a wear-through issue. Up to 10% gloss variance is considered completely normal between planks.

This warranty excludes damage by natural disasters. This warranty excludes floors in contact with moisture trapped beneath the floor. The general warranty is pro rata (25 years for flooring). A pro rata warranty is one that provides for a refund or credit that decreases according to a set formula as the warranty period progresses. A claim process takes up to 90 days to process, from the date Parkay Floors® is contacted. We require a detailed description with images of the issue that clearly show the problem. Contact Parkay Floors® dealer no later than 15 days after the discovery of the defect. Your dealer will arrange for proper inspection and coordinate a resolution of your claim.

ACS ENDURANCE 14MM TESTS



Acoustical Testing Laboratory



TEST REPORT

Impact Sound Transmission Test

ASTM E 492 – 09 (2016)e1 / ASTM E 989 – 21

On

**8 Inch (203 mm) Concrete Slab Floor- Ceiling Assembly
Overlaid with Underlayment Laminate Flooring – Comfortech
(Laminate Endurance Parkay)**

Report Number: NGC 7023081

Assignment Number: G-1867

Test Date: 10/10/2023

Report Approval Date: 10/11/2023

Submitted by:

Anthony J. Rivers
Acoustical Test Engineer


Reviewed by:

Michael J. Rizzo
General Manager

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory



NGC 7023081

10/11/2023


Revision Summary:

Date	SUMMARY
Approval Date: 10/11/2023	Original issue date: 10/11/2023 Original NGCTS report: NGC 7023081

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory



Report Number: NGC 7023081

Test Method: This test method is in accordance with American Society for Testing and Materials Standard Test Method for Laboratory Measurement of Sound Transmission Through Floor-Ceiling Assemblies Using the Tapping Machine - Designation: E 492-09 (2016)e1 / E 989-21.

The uncertainty limits of each tapping machine location met the precision requirements of section A1.4 of ASTM E 492-09 (2016).

Specimen Description: 8 inch concrete slab floor ceiling assembly overlaid with, Underlayment Laminate Flooring – Comfortech (Laminate Endurance Parkay).

The test specimen was a floor assembly and was observed to consist of the following:
All weights and dimension are averaged:

- 1 layer of, Underlayment Laminate Flooring – Comfortech (Laminate Endurance Parkay). The flooring was floating on the concrete slab. Measured thickness: 14.22 mm (0.56 in.). Measured weight: 9.91 kg/m² (2.03 PSF)
- 203.2 mm (8 in.) thick reinforced concrete slab, weighing: 488.2 kg/m² (100.00 PSF)

The overall weight of the test assembly is: 498.11 kg/m² (102.03 PSF)

The perimeter of the test frame was sealed with a rubber gasket and a sand filled trough.

The test frame was structurally isolated from the receiving room.

Specimen size: 3657.6 mm x 4876.8 mm (12 ft. x 16 ft.)


Conditioning: Concrete slab cured for a minimum of 28 days.

Test Results: The results of the tests are given on pages 4 and 5 of the report.

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory



Normalized impact sound pressure level						
Test: ASTM E 492 - 09 (2016)e1 / ASTM E 989 - 21						
Test Report: NGC7023081				Date: 10/10/2023		
Specimen Size [m ²]: 17.8						
Source room				Receiving room		
Volume [m ³]: 86				Volume [m ³]: 128		
Rm Temp [°C]: 25				Rm Temp [°C]: 25		
Humidity [%]: 50				Humidity [%]: 50		
Impact Insulation Class IIC :				53		
Sum of Unfavorable Deviations [dB]: 25						
Max. Unfavorable Deviation [dB]: 6				at 315 Hz		
Frequency	L _n	L ₂	d	Corr.	u.Dev.	ΔL _n
[Hz]	[dB]	[dB]	[dB/s]	[dB]	[dB]	
80	57	57.2	26.79	-0.2		1.66
100	57	58.6	18.83	-1.6		0.57
125	61	63.5	16.89	-2.5	2	1.17
160	63	65.8	17.46	-2.8	4	1.86
200	61	63.0	17.16	-2.0	2	0.95
250	60	62.1	16.75	-2.1	1	0.27
315	65	67.4	16.71	-2.4	6	0.93
400	61	63.1	18.51	-2.1	3	0.85
500	60	61.5	19.19	-1.5	3	0.41
630	58	59.5	20.28	-1.5	2	0.77
800	55	56.1	22.04	-1.1		0.58
1000	55	56.1	22.05	-1.1	1	0.85
1250	52	53.0	23.91	-1.0	1	0.53
1600	46	46.5	26.50	-0.5		0.18
2000	40	39.9	29.25	0.1		0.50
2500	34	33.5	30.68	0.5		0.66
3150	27	26.9	32.42	0.1		0.43
4000	22	21.5	36.77	0.5		0.21
5000	18	17.4	41.21	0.6		0.29
L _n = Normalized Sound Pressure Level, dB L ₂ = Receiving Room Level, dB d = Decay Rate, dB/second ΔL _n = Uncertainty for 95% Confidence Level						

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agent of the U.S. Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory

NVLAP
TESTING
NVLAP LAB CODE 200291-0
Accredited by the National Voluntary
Laboratory Accreditation Program for
the specific scope of accreditation.

Normalized impact sound pressure level

Test: ASTM E 492 - 09 (2016)e1 / ASTM E 989 - 21


Test Report: NGC7023081

Test Date: 10/10/2023

Specimen Size [m²]: 17.8

Impact Insulation Class IIC : 53

Frequency	L_n
[Hz]	[dB]
80	57
100	57
125	61
160	63
200	61
250	60
315	65
400	61
500	60
630	58
800	55
1000	55
1250	52
1600	46
2000	40
2500	34
3150	27
4000	22
5000	18



* Due to high insulating value of specimen, background levels limit results at these frequencies.

L_n = Normalized Sound Pressure Level, dB

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agent of the U.S. Government. This report may not be reproduced except in full, without written approval of the laboratory.

North Carolina State University is a land-grant university and a constituent institution of The University of North Carolina

NC STATE UNIVERSITY

Department of Forest Biomaterials
Campus Box 8005, Dan Allen Dr.
Raleigh, NC 27695-8005 USA

919.515.5807
919.515.6302(fax)

Hodges Wood Products Laboratory
919.515.2850

A Report to



from

North Carolina State University
Wood Products Laboratory


on

NALFA LF -01-2019 Thickness Swell,
ISO -24336 Thickness Swell, &
NALFA's Laminate Surface Swell Test – Assembled Joint

April 2023

Project Number: WPL -23-1934

Principal Investigator



Lyndsey Campbell

Department of Forest Biomaterials
Rm.110 Hodges Wood Products Lab
Campus Box 8005, Dan Allen Drive
Raleigh, NC 27695 -8005 USA
919-515-2881
Wp_techservices@ncsu.edu

IMPORTANT

- These tests were conducted according to the procedures described in NALFA standards LF 01-2019, ISO -24336, and NALFA's Laminate Surface Swell Test – Assembled Joint
- The test procedures and standards were designed for laminate flooring and their use with other products may produce misleading or irrelevant results.
- We do not certify a manufacturer's laminate flooring. We report only on the results of a given sample of laminate flooring which has been submitted to our laboratory for testing.
- The name of the University is not to be used in any type of advertising or promotional efforts.
- We have undertaken testing of laminate flooring as an independent testing laboratory largely as a service to the laminate flooring industry. However, our main purpose is that of education and research, which means that we cannot always respond quickly to requests for testing.

Department of Forest Biomaterials -- Hodges Wood Products Laboratory

NC STATE UNIVERSITY

WPL -23-1934

April 2023

p. 3

submittedone (1) sample for testing according to the test methods in NALFA LF01-2019, ISO -24336, and NALFA's Laminate Surface Swell Test – Assembled Joint

Sample coded as follows:

Sample #	Description
1	

Results to follow.

TEST RESULTS

NALFA LF -01 3.2 THICKNESS SWELL

Thickness swell reported as the average percent thickness change of the midpoints of all 4 edges of each of 2 specimens (measured at the midpoint of each edge – on the edge – and reported as percent of original thickness)

TEST RESULTS

NALFA LF-01		Product 1- Sample 1				Product 1- Sample 2			
3.2 Thickness Swell		A	B	C	D	A	B	C	D
Product 1	Initial thickness	7.94	7.92	7.94	7.93	7.9	7.9	7.89	7.9
	Final thickness	8.51	8.41	8.47	8.48	8.24	8.40	8.41	8.41
	Thickness Swell	7.18%	6.19%	6.68%	6.94%	4.30%	6.33%	6.59%	6.46%
	Average Thickness Swell	6.33%							

MINIMUM PERFORMANCE VALUES FROM THE STANDARD

NALFA/ANSI LF-01-2018 PERFORMANCE PROPERTIES AND VALUES					
2.1 PERFORMANCE PROPERTIES MINIMUM PERFORMANCE VALUES					
Usage Level		Residential	Light Commercial	Commercial	Heavy Commercial
Certification Level		1	2	3	4
TEST METHOD	PROPERTY				
3.2	Thickness Swell	≤ 18%	≤ 16%	≤ 16%	≤ 12%

Thickness swelling reported as the average percent thickness change of 3 measuring points of each of 4 specimens (measured perpendicular to the extreme edges per the standard, any pre-attached material removed, and reported as percent of original thickness)

ISO 24336		Replicate 1 (MD)			Replicate 2 (MD)			Replicate 3 (XMD)			Replicate 4 (XMD)		
Thickness Swelling													
Product 1	Point	A	B	C	A	B	C	A	B	C	A	B	C
	Initial thickness	7.93	7.94	7.94	7.87	7.88	7.88	7.94	7.92	7.94	7.90	7.95	7.90
	Final thickness	8.9	8.45	8.6	8.45	8.42	8.3	8.67	8.35	8.48	8.31	8.23	8.47
	Thickness Swell	12.2%	6.4%	8.3%	7.4%	6.9%	5.3%	9.2%	5.4%	6.8%	5.2%	3.5%	7.2%
	Total Thickness Swell	6.99%											

Department of Forest Biomaterials -- Hodges Wood Products Laboratory

NC STATE UNIVERSITY

WPL -23-1934

April 2023

p. 6

NALFA LAMINATE SURFACE SWELL TEST – ASSEMBLED JOINT

The NALFA Laminate Surface Swell- Assembled Joint Test is reported quantitatively and qualitatively. The quantitative measurement is reported as the final average thickness swell in both Point 1 and Points 1-4, but the performance criteria is based on Points 2-4. They are expressed as difference in the Recovery Swell measurement and Wet Swell measurement. The qualitative measurement is based on the grading of the Recovered joints enclosed in the PVC ring where the water was located.

TEST RESULTS

NALFA Surface Swell Worksheet										
Product 1										
Product Description: AGT Bella Neo/AGT Natura Select/AGT Pruva										
Specimen 1 Quantitative Results						Specimen 2 Quantitative Results				
Position	Initial height	Wet Height	Wet Swell	Recov. Height	Recov. Swell	Position	Initial height	Wet Height	Wet Swell	Recov. Swell
1	-0.01	-0.13	0.12	0.01	0.02	1	-0.15	-0.28	0.13	-0.08
2	-0.03	-0.11	0.08	0.01	0.04	2	-0.06	-0.18	0.12	-0.03
3	-0.02	-0.26	0.24	-0.04	0.02	3	-0.12	-0.14	0.02	-0.02
4	-0.11	-0.27	0.16	-0.12	0.01	4	-0.10	-0.25	0.16	-0.05
Average			0.16		0.02	Average			0.10	0.06
Initial Thickness Avg						Initial Thickness Avg				
Wet Height Avg						Wet Height Avg				
Wet Swell Avg						Wet Swell Avg				
Recov. Height Avg						Recov. Height Avg				
Recov. Swell Avg						Recov. Swell Avg				
Specimen # 1 Qualitative Result						Specimen # 2 Qualitative Result				
Wet						Sample				
Recov.						Recov.				

Results Summary		
	Wet	Recov.
Final Avg. Thick. Swell (Pos 2-4)	0.13	0.04
Final Avg Position 1 Thickness Swell	0.13	0.05
Qualitative Rating Spec 1	2	1
Qualitative Rating Spec 2	2	1


Grade:
1 = No change - No noticeable change in edge swell or panel surface lift
2 = Slight swelling - Slight swelling, small ridge along one or more joints, very little if any panel surface lift
3 = Moderate - Noticeable edge swelling and some panel surface lift extending away from joint
4 = Objectional - Severely raised edge and swelling extending noticeably under the panel surface
5 = Invalid Test - Water leaked out of the ring, leaving no continuous film of water inside the ring (this grade is given even if there is no swell of the edge joint)

MINIMUM PERFORMANCE VALUES FROM THE STANDARD

NALFA Topical Moisture (summary table)			Results	Minimum Performance
1	Recovered Qualitative Rating	1-5		≤2
	Measured Recovered Average (mm)	mm		≤0.3
*Minimum performance values only based on points 2-4 (P2-4)				



Acoustical Testing Laboratory



TEST REPORT

Sound Transmission Loss Test

ASTM E 90 – 09 (2016) / E 413 – 22

On

**8 Inch (203 mm) Concrete Slab Floor- Ceiling Assembly
Overlaid with Underlayment Laminate Flooring – Comfortech
(Laminate Endurance Parkay)**

Report Number: NGC 5023041

Assignment Number: G-1867

Test Date: 10/10/2023

Report Approval Date: 10/11/2023

Submitted by:

Anthony J. Rivers
Acoustical Test Engineer


Reviewed by:

Michael J. Rizzo
General Manager

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory



NGC 5023041

10/11/2023


Revision Summary:

Date	SUMMARY
Approval Date: 10/11/2023	Original issue date: 10/11/2023 Original NGCTS report: NGC 5023041

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory



Report Number: NGC 5023041

Test Method: This test method conforms explicitly with the American Society for Testing and Materials Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements – Designation: E 90 - 09 (2016) / E 413 - 22.

Specimen Description: 8 inch concrete slab floor ceiling assembly overlaid with, Underlayment Laminate Flooring – Comfortech (Laminate Endurance Parkay).

The test specimen was a floor assembly and was observed to consist of the following:
All weights and dimension are averaged:

- 1 layer of, Underlayment Laminate Flooring – Comfortech (Laminate Endurance Parkay). The flooring was floating on the concrete slab. Measured thickness: 14.22 mm (0.56 in.). Measured weight: 9.91 kg/m² (2.03 PSF)
- 203.2 mm (8 in.) thick reinforced concrete slab, weighing: 488.2 kg/m² (100.00 PSF)

The overall weight of the test assembly is: 498.11 kg/m² (102.03 PSF)

The perimeter of the test frame was sealed with a rubber gasket and a sand filled trough.

The test frame was structurally isolated from the receiving room.

Specimen size: 3657.6 mm x 4876.8 mm (12 ft. x 16 ft.)

Conditioning: Concrete slab cured for a minimum of 28 days.

Test Results: The results of the tests are given on pages 4 and 5 of the report.

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory

NVLAP
TESTING
NVLAP LAB CODE 200291-0
Accredited by the National Voluntary
Laboratory Accreditation Program for
the specific scope of accreditation.

Sound Transmission Loss Test Data							
Test: ASTM E 90 - 09 (2016) / ASTM E 413 - 22							
Test Report: NGC 5023041				Date: 10/10/2023			
Specimen Size [m²]: 17.8							
Source room				Receiving room			
Volume [m³]: 86				Volume [m³]: 128			
Rm Temp [°C]: 25				Rm Temp [°C]: 25			
Humidity [%]: 50				Humidity [%]: 50			
Sound Transmission Class STC :				54			
Sum of Unfavorable Deviations [dB]: 15							
Max. Unfavorable Deviation [dB]: 8				at 125 Hz			
Frequency [Hz]	TL [dB]	L1 [dB]	L2 [dB]	d [dB/s]	Corr. [dB]	u.Dev. [dB]	ΔTL [± dB]
80	43	106.7	66.9	27.4	3.2		1.31
100	39	109.2	74.3	19.6	4.1		1.08
125	30	107.7	82.2	17.5	4.4	8	1.53
160	50	112.0	66.4	17.1	4.4		0.53
200	48	110.0	67.0	18.4	5.0		0.90
250	48	106.4	63.5	17.0	5.1		0.49
315	49	105.0	61.1	17.1	5.1	1	0.98
400	51	103.4	56.6	18.3	4.3	2	0.68
500	55	105.1	54.5	19.2	4.4		0.30
630	54	104.3	54.6	20.1	4.3	1	0.69
800	54	104.0	53.7	21.6	3.7	2	0.73
1000	56	100.8	48.7	22.1	3.8	1	0.85
1250	59	98.8	42.9	23.8	3.1		0.55
1600	64	99.8	39.2	26.3	3.4		0.46
2000	68	101.5	35.8	29.4	2.3		0.29
2500	69	102.9	36.3	30.9	2.4		0.56
3150	71	102.2	33.8	32.4	2.6		0.58
4000	73	98.7	27.2	36.3	1.6		0.32
5000	76	92.2	17.0	41.9	0.8		0.20
TL = Sound Transmission Loss, dB L1 = Source Room Level, dB L2 = Receiving Room Level, dB d = Decay Rate dB/second Δ TL = Uncertainty for 95% Confidence Level							

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agent of the U.S. Government. This report may not be reproduced except in full, without written approval of the laboratory.



Acoustical Testing Laboratory

NVLAP
TESTING
NVLAP LAB CODE 200291-0
Accredited by the National Voluntary
Laboratory Accreditation Program for
the specific scope of accreditation.

Sound Transmission Loss Test Data

Test: ASTM E 90 - 09 (2016) / ASTM E 413 - 22

Test Report: NGC 5023041


Test Date: 10/10/2023

Specimen Size [m²]: 17.8

Sound Transmission Class STC = 54

Frequency [Hz]	TL [dB]	ΔTL [+/- dB]
80	43	1.31
100	39	1.08
125	30	1.53
160	50	0.53
200	48	0.90
250	48	0.49
315	49	0.98
400	51	0.68
500	55	0.30
630	54	0.69
800	54	0.73
1000	56	0.85
1250	59	0.55
1600	64	0.46
2000	68	0.29
2500	69	0.56
3150	71	0.58
4000	73	0.32
5000	76	0.20

* Due to high insulating value of specimen, background levels limit results at these frequencies.



TL = Sound Transmission Loss, dB
Δ TL = Uncertainty for 95% Confidence Level
The test sample was tested in one direction

The results reported above apply to specific samples submitted for measurement. No responsibility is assumed for performance of any other specimen. The laboratory's accreditation or any of its test reports in no way constitute or imply product certification, approval, or endorsement by NVLAP, NIST or any agent of the U.S. Government. This report may not be reproduced except in full, without written approval of the laboratory.

