

Waterproof

Safe to use in kitchens and bathrooms for modern looks throughout the home.

No Acclimation Required

ProGen may be used immediately. ProGen is extremely stable and has no temperature limitations, so it's great for 3-Season rooms.

Durable

Supports the everyday life of a busy, active household, like kids, pets, high heels and heavy furniture.

Easy Installation

ProGen does not require power tools and can be simply cut with a utility knife. Its fast-locking click system provides a low-cost, low-mess installation, even over existing floors.

No Transitions Required

ProGen is so stable, no transitions are required between rooms or in large spaces.

Quiet

IIC rating of 68 means superior sound absorption to drastically improve overall comfort.

Finish with Style

Finish the install with coordinating trims and moldings to help your customer create a seamless, cohesive look. We also offer **matching** flush stair treads and returns with VersaCap™, made from the actual floor!



















ProGen[™] RIGID CORE FLOORING



Nordic XXL Reflection 270281010



Sequoia XXL Canyon 270281011



Ridge 270304001



Kensington XL Manor 270304002



Mirage XL Luna 270304003



Mirage XL Soleil 270304004



Mirage XL Terre 270304005



Spicebark Hickory Fumed 270266016



Spicebark Hickory Comino 270266017



Milled Oak Copper 270266018



West Oak Natural 270266021 PB



West Oak Drift 270266024 PB



Cerused Oak Powder 270265013



Vista Oak Limed Natural 270265015



Chevron Tawny 270265025



Vale Oak Dove 270265027 PB



Harmony Elm Cocoa 270265028 РΒ



Rock Maple Medio 270264012



Durham Pine Tavern 270264013



Stained Maple Carmine 270264015



Arabescato Illusion 270288008 PB



Fleury Travertine Verona 270288000



Bordeaux Chateau 270288009



Villa Slate Spire 270288001



Bordeaux Nouveau 270288010



Calacatta Marble Pearl 270288006 PB



Marquina Nero 270288012 PB



Varenna Stone Fossil 270288007 PB



Travertino Horizon



270288013 PB



Marble Nouveau Avalanche 270288014



PB Painted Bevel



Specifications							
Tatal Thickness	0.107" (5 ,,,,,,,,)	Оросп					
Total Thickness	0.197" (5 mm)						
ProGen Core Technology IXPE Acoustical Backing	0.157" (4 mm)						
	0.039" (1 mm) 20 mils/.020"						
Wear Layer Thickness Material							
Reusable Content	Ortho-Phthalate-Free, 100% Virgin Material 100% Reclaimable						
Reusable Content	5" x 48" 7" x 48" 7" x 60" 9"x60" 9" x 72" 12" x 24"						
Plank Size	(127 x 1220 mm)	(181 x 1220 mm)	(181 x 1520 mm)	(228 x 1524 mm)	(228 x 1829 mm)	(305 x 610 mm)	
Sq. Ft. per Carton	26.68 sq. ft.	28.52 sq. ft.	29.61 sq. ft.	29.82 sq. ft.	26.91 sq. ft.	28.03 sq. ft.	
Planks per Carton	16	12	10	8	6	14	
Cartons per Pallet	56	50	40	44	52	54	
Lbs. per Carton	42 lbs.	44 lbs.	45 lbs.	48.1 lbs.	43.4 lbs.	45 lbs.	
ASTM F3261 (Rigid Polymeric Core) Spec.	Class 1, Type A or B, Grade 1, Backing Class B						
ASTM F2199 (Dimensional Stability)	Passes						
ASTM F1914 (Residual Indentation)	Passes						
ASTM F1514 (Heat Stability)	Passes						
ASTM F1515 (Light Stability)	Passes						
ASTM E2179 (Impact Sound Reduction)	Δ IIC ≥ 20 dB						
ASTM E492 (6" Concrete Slab w/a Drop Ceiling)	IIC 68						
ASTM F925 (Resistance to Chemicals)	Passes						
ASTM D5116 (VOC Requirements)	Passes < 0.1 mg/m³						
Scratch/Scuff/Abrasion Properties	Excellent						
Installation System	Click System: Uniclic®						
Residential Warranty	Lifetime						
Light Commercial Warranty	15-Year						
3-Seasons Warranty	10-Year						
Certification	FloorScore® and Assure Certified™						

Installation

Floating Floor	Quick and Simple Angle-Angle Click		
Above/At/Below Grade	✓		
No Acclimation	✓		
No Transition Required	✓		
No Temperature Limitations/ Direct Sunlight Install	✓		
Acoustic Rating	Total IIC of 68 (6" Concrete Slab + Suspended Ceiling)		









Tarkett North America

30000 Aurora Road | Solon, OH 44139 USA: 1-877-TARKETT (1-877-827-5388) Canada: 1-877-436-6267

www. Tarkett Home. com

















