

ProTuff™ is a revolutionary flooring option perfect for multi-family living. ProTuff's dense, compact foam core helps **prevent indentation and improves tear resistance.** Plus, it's full urethane wear layer makes it **resistant to scratches, scuffs, and stains.** Like all Tarkett Home sheet vinyl products, ProTuff™ is **waterproof** - it's perfect for wet areas like bathrooms, kitchens, and laundry rooms. This floor is also CERTIFIED **asthma & allergy friendly**®, making it a better choice for your residents, including those impacted by asthma and allergies.

### **Tough & Carefree**

ProTuff's 12 mil wearlayer gives it superior protection against tears, scratches, and scuffs. Plus, its full urethane finish makes it easy to clean.

### **Built to Last**

An ultra-dense foam backing gives  $ProTuff^{\mathsf{m}}$  its strength. This floor stands up to kids, pets, high heels, and heavy furniture.

#### **Easy Installation**

ProTuff™ is more flexible and 25% lighter than competitive sheet products. It is easier to manage and install without sacrificing performance.















# Tarkett FiberFloor® - ProTuff™



45001 | Barnwood 36" x 72", DNR WB: Warm Grey or Dark Stone



36" x 72", DNR WB: Warm Grey



45011 | American Chestnut | 45012 | American Chestnut | 45021 | Dakota 36" x 72", DNR WB: Graphic Charcoal or Dove Grey



36" x 36", 18" Drop, DNR WB: Warm Grey



45022 | Dakota 36" x 36", 18" Drop, DNR WB: Warm Grey



45031 | Lexington 36" x 36", 18" Drop, DNR WB: Warm Grey or Dark Stone



45041 | Brentwood 36" x 48", 12" Drop, DNR



45042 | Brentwood 36" x 48", 12" Drop, DNR WB: Warm Grey or Dove Gre



45051 | Hickory Tile 36" x 36", 18" Drop, DNR WB: Warm Grey or Dove Grey



45061 | Barn Jazz 36" x 72", 18" Drop, DNR WB: Warm Grev



45062 | Barn Jazz 36" x 72", 18" Drop, DNR WB: Dove Grev



45071 | Capri Almond 36" x 48". DNR WB: Warm Grev



45091 | Rich Onvx 36" x 36" DNR WB: Bright White or Dove Grey



45111 | Ridaeline 36" x 72". DNR WB: Dove Grev

**Specifications** 



45112 | Ridgeline 36" x 72", DNR WR: Warm Grev



45121 | Roca Bone 36" x 72", DNR WB: Bright White or Dove Grey



45122 | Roca Ashes 36" x 72", DNR WB: Warm Grev



45191 | Tumbled Stone 36" x 36", 12" Drop, DNR



1.			TO A STATE OF THE PARTY OF THE
RICH ONYX	CICLE	45091	

### **Healthier Home**

This product has been certified to meet the requirements of these flooring products certification programs for indoor air q











ation uality.	
floor core	
10	

, and the second se	
Series	45XXX
Nominal Total Thickness	55 mils (0.055"/1.40 mm)
Wear Layer Thickness	12 mils (0.012"/0.31 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6m)
Maximum Roll Size	205 sq. yd. (171 m²)
Weight per Sq. Yd.	2.71 lbs (1.23 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm <sup>2</sup>
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6,4mm)
ASTM F925 (Staining)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm²)
ASTM F1514 (Heat Stability)	ΔΕ<8
ASTM F1515 (Light Stability)	ΔΕ<8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 14 dB
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One™ or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum	Yes, =/>0.010" wear layer
FloorScore® Certification	SCS-EC10.3-2014: SCS-FS-02746

## **Tarkett North America**

www.TarkettHome.com









Connect with us @ TarkettHome



Scan this code to visit www.TarkettHome.com/ProTuff

The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of the ASTHMA AND ALLERGY FOUNDATION OF AMERICA and ALLERGY STANDARDS LTD.