

PRODUCT SPECIFICATIONS	
Style Number	L80KD
Style Name	Loose Lay Plank
Construction	Fiberglass Reinforced Recycled PVC
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	5mm
Attached Cushion	Non-Skid Backing
FEATURES	
Plank Edge	Square Edge
Texture	Standard Embossing
Plank Size	6" X 48"
Installation	Loose Lay / Glue Down
TESTING	
Impact Sound Conduction / ASTM E492-09	IIC 47
Sound Transmission Class /ASTM E90-09	STC 53
Slip Resistance / ASTM D2047	0.84 Dry / 0.86 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450
WARRANTIES	
	Lifetime Residential
	10 Year Commercial
ENVIRONMENTAL	
Indoor Air Quality	FloorScore[®] Certified