

PRODUCT SPECIFICATIONS	
Style Number	R062D
Style Name	Equity Plank
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	6mm (5mm RSPC/1 mm IXPE)
Attached Cushion	1 mm IXPE
FEATURES	
Plank Edge	Micro Bevel
Texture	EIR (Embossed in Register)
Plank Size	9" x 60"
Installation	Floating/Uniclic Locking System
TESTING	
Impact Sound Conduction / ASTM E492-09	IIC 60
Sound Transmission Class /ASTM E90-09	STC 53
Slip Resistance / ASTM D2047	Dry 0.76 / Wet 0.84
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F 925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450
WARRANTIES	
	Lifetime Residential
	10 Year Commercial
ENVIRONMENTAL	
Indoor Air Quality	GREENGUARD Gold Certified
	FloorScore® Certified