

PRODUCT SPECIFICATIONS	
Style Number	R070A
Style Name	Liberty Plank
Construction	Class III High Performance LVP
Wear Layer Finish	Ceramic Urethane
Wear Layer Thickness	20 mil
Overall Thickness	5.5mm (4.5mm RSPC Core)
Attached Cushion	1mm Grey XPO
FEATURES	
Plank Edge	Painted Bevel
Texture	Wood Grain
Plank Size	7.69" X 60"
Installation	Floating/I4F Locking system
TESTING	
Impact Sound Conduction / ASTM E492-09	IIC 61
Sound Transmission Class /ASTM E90-09	STC 53
Slip Resistance / ASTM D2047	.90 Dry / .91 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450
Smoke Density / ASTM E662 Non-Flaming	Pass, <450
WARRANTIES	
	Lifetime Residential
	10 Year Commercial
ENVIRONMENTAL	
Indoor Air Quality	FloorScore® Certified