

<b>PRODUCT SPECIFICATIONS</b>	
Style Number	<b>R071D</b>
Style Name	<b>Panoramic</b>
Construction	<b>High Performance LVP</b>
Wear Layer Finish	<b>Urethane Coating</b>
Wear Layer Thickness	<b>20 mil</b>
Overall Thickness	<b>6mm (5mm RSPC/1mm IXPE)</b>
Attached Cushion	<b>1mm IXPE</b>
<b>FEATURES</b>	
Plank Edge	<b>Painted Bevel</b>
Texture	<b>Wood Grain Embossed</b>
Plank Size	<b>7" x 60"</b>
Installation	<b>Floating/Uniclic Locking System</b>
<b>TESTING</b>	
Impact Sound Conduction / ASTM E492-09	<b>IIC 61</b>
Sound Transmission Class /ASTM E90-09	<b>STC 53</b>
Slip Resistance / ASTM D2047	<b>&gt;.50</b>
Dimensional Stability / ASTM F2199	<b>Pass</b>
Residual Indentation / ASTM F1914	<b>Pass</b>
Static Load Limit / ASTM F970	<b>Pass</b>
Resistance to Heat / ASTM F1514	<b>Pass</b>
Resistance to Light / ASTM F1515	<b>Pass</b>
Resistance to Chemicals / ASTM F925	<b>Pass</b>
Radiant Flux / ASTM E648	<b>&gt;0.45 watts/cm<sup>2</sup>, NFPA Class I</b>
Smoke Density / ASTM E662	<b>Pass, &lt;450</b>
<b>WARRANTIES</b>	
	<b>Lifetime Residential</b>
	<b>10 Year Commercial</b>
<b>ENVIRONMENTAL</b>	
Indoor Air Quality	<b>GREENGUARD Gold certified</b>
	<b>FloorScore® certified</b>