

PRODUCT SPECIFICATIONS	
Style Number	W095D
Style Name	Traditions
Construction	High Performance LVP
Wear Layer Finish	Urethane UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	6.5mm (4mm WPC/1mm IXPE/1.5mm Vinyl Top)
Attached Cushion	1mm IXPE Cross Linked Polyethelene
FEATURES	
Plank Edge	Micro Bevel
Texture	EIR (Embossed In Register)
Plank Size	3.26" Width/Mixed Lengths 19.69"/39.37"/60"
Installation	Floating/Uniclic Locking System
TESTING	
Impact Sound Conduction / ASTM E492-09	IIC 61
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.86 Dry/0.90 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450
WARRANTIES	
	Lifetime Residential
	10 Year Commercial
ENVIRONMENTAL	
Indoor Air Quality	GREENGUARD Gold Certified
	FloorScore® Certified