

<b>PRODUCT SPECIFICATIONS</b>	
Style Number	<b>W11L</b>
Style Name	<b>Timeless Plank</b>
Construction	<b>Class III High Performance LVP</b>
Wear Layer Finish	<b>Urethane with Double UV Coating</b>
Wear Layer Thickness	<b>12 mil</b>
Overall Thickness	<b>6.5mm (4mm WPC/1mm IXPE/1.5mm Vinyl Top)</b>
Attached Cushion	<b>1mm IXPE</b>
<b>FEATURES</b>	
Plank Edge	<b>Square Edge</b>
Texture	<b>Standard Embossing</b>
Plank Size	<b>6" X 48"</b>
Installation	<b>Floating/Uniclic Locking System</b>
<b>TESTING</b>	
Impact Sound Conduction / ASTM E492-09	<b>IIC 62</b>
Sound Transmission Class /ASTM E90-09	<b>STC 53</b>
Slip Resistance / ASTM D2047	<b>0.86 Dry</b>
Dimensional Stability / ASTM F2199	<b>Pass</b>
Residual Indentation / ASTM F1914	<b>Pass</b>
Static Load ASTM F970	<b>Pass</b>
Resistance to Heat / ASTM F1514	<b>Pass</b>
Resistance to Light / ASTM F1515	<b>Pass</b>
Resistance to Chemicals / ASTM F925	<b>Pass</b>
Radiant Flux / ASTM E648	<b>&gt;0.45 watts/cm<sup>2</sup>, NFPA Class I</b>
Smoke Density / ASTM E662	<b>Pass, &lt;450</b>
<b>WARRANTIES</b>	
	<b>Lifetime Residential</b>
	<b>10 Year Commercial</b>
<b>ENVIRONMENTAL</b>	
Indoor Air Quality	<b>GREENGUARD Gold Certified</b>
	<b>FloorScore® Certified</b>