



BEACHSIDE OAK ESPC68304C



CAPE COD ESPC68332C



COCO BEACH ESPC68323C



COTTONWOOD ESPC68318C



DESTIN OAK ESPC68381C



DUN* ESPC68333C




FARMHOUSE OAK ESPC68358C



GINGER OAK ESPC68395C



GOLDEN OAK ESPC68338C



HAY* ESPC68377C



HOMESTEAD OAK ESPC68301C



LODGE MAPLE ESPC68313C



PECAN ESPC68316C



PEPPERCORN OAK ESPC68305C



SALEM HICKORY ESPC68362C



SEASHORE* ESPC68322C



SORREL* ESPC68311C



SOUTHERN PECAN ESPC68363C



SPALTED BEACH ESPC68385C



WASHED HICKORY ESPC68366C



GEORGIA OAK ESPC68380C



SEDONA OAK ESPC68371C

SIZE
9" x 60" *9 1/4" x 60"

PROFILE
EIR embossed + exclusive soft pil-
lowed edges

WEAR LAYER
28 mil

INSTALLATION
Click

PRODUCT WARRANTIES
Lifetime Residential, Stucture,
Waterproof, No Cupping Warranty
15-Year Commercial Warranty

PACKAGING
40' Container: 19 sf/ct - 5 pc/ct - ~52
lbs/ct - 60 ct/pl - 1,140 sf/pl - 17 pl/
container - 19,380 sf/container
*40' Container: 19.5 sf/ct - 5 pc/ct -
~52 lbs/ct - 64 ct/pl - 1,248 sf/pl - 16
pl/container - 19,968 sf/container

TESTING
Reaction to Fire EN13501-1: Pass
Bfl-S1
Resistance to Heat ASTM F1514-03:
Pass ^F<8
Static Load ASTM F970-07: Pass <
5 mils
Coefficient of Friction: Pass > 0.5
Standard Neolite
and leather, wet and dry
Color Fastness to artificial light ISO
105-B02:

Pass > 5
Color Fastness to rubbing ISO 105-
E01: Pass >3 wet, >4 dry
FloorScore Certified
Slip Resistant

SOUND RATING
IIC 68
STC 66