

BEAUTIFUL AND HEALTHY FOR THOSE YOU LOVE MOST.

TritonTuff™

LUXURY SHEET FLOORING



CANYON SLATE | ZINC | 21032

TritonTuff™ combines traditional, compact fiberglass reinforced flooring with a super-strong textile back, Beyond Tough™, making it 75% stronger than traditional luxury sheet floor products. With a 60 mil thickness and a 10 mil wearlayer, this is the perfect combination of value and **PERFORMANCE**, making it ideal for builder and multi-family projects. This floor is also CERTIFIED **asthma & allergy friendly®**, making it a better choice for your residents, including those impacted by asthma and allergies.



SUPER STRONG



WATERPROOF



THICKNESS



CLEANS EASILY



PET & FAMILY FRIENDLY

ORTHO-PHTHALATE FREE

 **Tarkett**
Home

TritonTuff™

LUXURY SHEET FLOORING



21001 | Pompano
Fog
36" x 36"
18" Drop, DNR



21021 | Cement Tile
Whisper
36" x 72"
DNR



21031 | Canyon Slate
Cloud
36" x 48"
12" Drop, DNR



21032 | Canyon Slate
Zinc
36" x 48"
12" Drop, DNR



21041 | Carrara
Alabaster
36" x 36"
18" Drop, DNR



21051 | Clearwater Oak
Glacier
36" x 36"
18" Drop, DNR



21052 | Clearwater Oak
Mink
36" x 36"
18" Drop, DNR



21061 | Herringbone
Wolf
36" x 72"
DNR



21071 | Remix
Smoke
48" x 72"
DNR



21072 | Remix
Bronze
48" x 72"
DNR



21081 | Berkshires Oak
Mist
36" x 36"
14.4" Drop, DNR



21082 | Berkshires Oak
Buff
36" x 36"
14.4" Drop, DNR



21083 | Berkshires Oak
Gunstock
36" x 36"
14.4" Drop, DNR



21084 | Berkshires Oak
Harbour Brown
36" x 36"
14.4" Drop, DNR



21111 | Hutchison
Powder
36" x 18"
18" Drop, DNR



21121 | Barn Jazz
Prairie
36" x 72"
18" Drop, DNR



21152 | Farmhouse Pine
Harvest
36" x 48"
12" Drop, DNR



21161 | Longwood
Cocoa
36" x 36"
18" Drop, DNR



Stands up to kids and pets.
The Beyond Tough™ backing protects
against rips, tears and gouges.



ORTHO-PHTHALATE
FREE

Specifications

Series	21XXX
Nominal Total Thickness	60 mils (1.52 mm)
Wear Layer Thickness	10 mils (0.254 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6 m)
Standard Roll Size	179 sq. yd. (149.7 m²)
Weight per Sq. Yd.	2.22 lbs. (1.007 kg)
ASTM F1303	Type 1, Grade 3, Class C
ASTM D2047 (Slip)	>0.5
ASTM E648 (Fire)	>0.45 W/cm²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	Passes
ASTM F925 (Staining)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm²)
ASTM F1514 (Heat Stability)	Δ E < 8
ASTM F1515 (Light Stability)	Δ E < 8
ASTM E2179 (Impact Sound Reduction)	Δ IIC 16 dB
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One™
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum	Yes, ≥/0.010" wear layer
FloorScore® Certification	SCS-EC10.3-2014: SCS-FS-02746
CERTIFIED asthma & allergy friendly ® by Allergy Standards Ltd and the Asthma and Allergy Foundation of America (AAFA)	
Certificate ASR-1155-03	

Tarkett North America

www.TarkettHome.com



Connect with us
@ TarkettHome



Scan this code to visit
www.TarkettHome.com/TritonTuff

The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of the ASTHMA AND ALLERGY FOUNDATION OF AMERICA and ALLERGY STANDARDS LTD.

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett Home dealer to view an actual product sample.