



756 Montgomery

	US Units	Metric Units
Style Number	1048V	
Construction	Residential Resilient - Sheet	
Profile	Direct Glue	
Overall Thickness	0.065"	1.651 mm
Wear Layer Thickness	10 mil (0.01")	0.3 mm
Finish	Opticlean Urethane	
Installation Methods	Direct Glue	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	10 Year Residential Sheet Vinyl Limited Warranty	
Installation	Residential Sheet Flooring Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	

Colors




146 Borbeck
Pattern: 39Inch W x 39Inch L
Drop: 10Inch




254 Barnes
Pattern: 39Inch W x 39Inch L
Drop: 10Inch




567 Devon
Pattern: 39Inch W x 59Inch L
Drop: 30Inch



583 Noble
Pattern: 39Inch W x 39Inch L



744 Algon
Pattern: 39Inch W x 39Inch L



756 Montgomery
Pattern: 39Inch W x 59Inch L

Suggested Adhesive

Style Name	Style Number
SHAW 350 PS ADH 4G	024VS
SHAW 350 PS ADH 1G	053VS
SHAW SV-1200 1 GAL	100SA
SHAW SV-1200 4 GAL	101SA